



**DATE: 19 March 2019**

**I.T.L. (PRODUCT TESTING) LTD.  
FCC/IC Radio Test Report**

for

**Pointer Telocation**

**Equipment under test:**

**Asset Tracking Device**

**CelloTrack 10Y LTE C1 NA**

**P/N: GC9773000**

Tested by:

M. Zohar

Approved by:

D. Shidlowsky

This report must not be reproduced, except in full, without the written permission of I.T.L. (Product Testing) Ltd.

This report relates only to items tested.



## Measurement/Technical Report for Pointer Telocation

Asset Tracking Device

**CelloTrack 10Y LTE C1 NA**

**FCC ID: 2AG69CTLL**  
**IC: 9975A-CTLL**

This report concerns: Original Grant:  
Class II change: X  
Class I change:

Equipment type: FCC – Digital Transmission System  
IC – Low Power Device (2400-2483.5MHz)

Limits used: 47CFR Part 22, 24, 27

Measurement procedure used is ANSI C63.10 2013

Substitution Method used as in ANSI/TIA-603-D: 2010.

Application for Certification  
prepared by:  
R. Pinchuck  
ITL (Product Testing) Ltd.  
1 Bat Sheva St.  
Lod 7120101  
Israel  
E-mail rpinchuck@itlglobal.org

Applicant for this device:  
(different from "prepared by")  
Igor Rogov  
Pointer Telocation  
14 Hamelacha, PO Box 11473  
Rosh Haain  
Israel  
Tel: +972 73 2622320  
E-mail: Igorr@pointer.com



## TABLE OF CONTENTS

<b>1.</b>	<b>GENERAL INFORMATION</b> -----	<b>4</b>
	1.1 Administrative Information.....	4
	1.2 List of Accreditations .....	5
	1.3 Product Description .....	6
	1.4 Test Methodology .....	6
	1.5 Test Facility .....	6
	1.6 Measurement Uncertainty .....	6
<b>2.</b>	<b>SYSTEM TEST CONFIGURATION</b> -----	<b>7</b>
	2.1 Justification.....	7
	2.2 EUT Exercise Software .....	7
	2.3 Special Accessories .....	7
	2.4 Equipment Modifications .....	7
	2.5 Configuration of Tested System.....	7
<b>3.</b>	<b>TEST SET-UP PHOTOS</b> -----	<b>9</b>
<b>4.</b>	<b>INTERMODULATION RADIATED</b> -----	<b>10</b>
	4.1 Test Procedure.....	10
	4.2 Test Limit.....	10
	4.3 Test Results.....	10
	4.4 Test Instrumentation Used; Radiated Measurements Intermodulation.....	12
<b>5.</b>	<b>ANTENNA INFORMATION/GAIN</b> -----	<b>13</b>
<b>6.</b>	<b>RF EXPOSURE/SAFETY</b> -----	<b>14</b>
<b>7.</b>	<b>APPENDIX A - CORRECTION FACTORS</b> -----	<b>15</b>
	7.1 Correction factor for RF CABLE for Semi Anechoic Chamber.....	15
	7.2 Correction factors for biconical antenna – ITL # 1356 .....	16
	7.3 Correction factors for log periodic antenna – ITL # 1349.....	17
	7.4 Correction factors for Double –Ridged Waveguide Horn ANTENNA.....	18



# 1. General Information

## 1.1 Administrative Information

Manufacturer:	Pointer Telocation
Manufacturer's Address:	14 Hamelacha, PO Box 11473 Roash Haain, Israel Tel: +972 73 2622320
Manufacturer's Representative:	Igor Rogov
Equipment Under Test (E.U.T):	Asset Tracking Device
PMN:	CelloTrack 10Y LTE C1 NA
Equipment Serial No.:	2310289
HVIN:	3000
Date of Receipt of E.U.T:	February 03, 2019
Start of Test:	February 05, 2019
End of Test:	February 06, 2019
Test Laboratory Location:	I.T.L (Product Testing) Ltd. 1 Batsheva St, Lod, Israel 7116002
Test Specifications:	FCC Part 22, 24, 27



## **1.2 List of Accreditations**

The EMC laboratory of I.T.L. is accredited by/registered with the following bodies:

1. The American Association for Laboratory Accreditation (A2LA) (U.S.A.), Certificate No. 1152.01.
2. The Federal Communications Commission (FCC) (U.S.A.), FCC Designation Number is IL1005.
3. The Israel Ministry of the Environment (Israel), Registration No. 1104/01.
4. Industry Canada (Canada), IC File No.: 46405-4025; Site No. IC 4025A-1, IC 4025A-2.

I.T.L. Product Testing Ltd. is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this test report have been determined in accordance with I.T.L.'s terms of accreditation unless stated otherwise in the report.

### 1.3 **Product Description**

The CelloTrack 10Y is an asset tracking device with up to 10 years of operational lifetime, using a non-rechargeable battery, including wireless sensor connectivity (with the MultiSenses). The CelloTrack 10Y is ideal for long term remote applications, requiring minimum or no maintenance at all. Suitable for application with extreme operating temperatures in which charging and performance are challenging.

### 1.4 **Test Methodology**

Both conducted and radiated testing were performed according to the procedures in ANSI C63.10 2013 and ANSI/TIA-603-D: 2010. Radiated testing was performed at an antenna to EUT distance of 3 meters.

### 1.5 **Test Facility**

Both conducted and radiated emissions tests were performed at I.T.L.'s testing facility in Lod, Israel. I.T.L.'s EMC Laboratory is accredited by A2LA, certificate No. 1152.01 and its FCC Designation Number is IL1005.

### 1.6 **Measurement Uncertainty**

#### **Conducted Emission**

Conducted Emission (CISPR 11, EN 55011, CISPR 22, EN 55022, ANSI C63.4)

0.15 – 30 MHz:

Expanded Uncertainty (95% Confidence, K=2):

± 3.44 dB

#### **Radiated Emission**

Radiated Emission (CISPR 11, EN 55011, CISPR 22, EN 55022, ANSI C63.4)

for open site:

30-1000MHz:

Expanded Uncertainty (95% Confidence, K=2):

± 4.96 dB

1 GHz to 6 GHz

Expanded Uncertainty (95% Confidence, K=2):

±5.19 dB

>6 GHz

Expanded Uncertainty (95% Confidence, K=2):

±5.51 dB

## 2. System Test Configuration

### 2.1 Justification

1. The E.U.T. was originally FCC certified on 07/02/2018 under FCC ID: 2AG69CTLL and IC certified on 7/24/2018 under IC: 9975A-CTLL.
2. The E.U.T contains 2 transceivers: a BLE, as certified above, and a 4G cellular approved module LTE/WCDMA module, manufactured by Gemalto M2M GmbH, model Cinterion ELS61-US, FCC ID: QIPELS61-US, IC: 7830A-ELS61US.
3. The manufacturer wishes to replace the above Gemalto 4G cellular module with the following LTE/WCDMA 4G module, also manufactured by Gemalto M2M GmbH, model Cinterion ELS61-USA, FCC ID: QIPELS61-USA, IC: 7830A-ELS61USA. See customer's Declaration of Change on following page.
4. A C2PC is requested based on this change. Intermodulation Radiated testing was performed and RF exposure was calculated.
5. The E.U.T. met the requirements of a C2PC.
6. Testing was performed with simultaneous transmission at maximum power and at the following frequencies:  
For BLE: 2402.0MHz  
For 4G cellular: 1910.0MHz
7. Testing was performed in 3 orthogonal orientations to find the "worst case" radiation which was determined to be the X axis.
8. The E.U.T. was evaluated while battery operated (3.6 Vdc).

### 2.2 EUT Exercise Software

No exercise software was needed in order to achieve compliance.

### 2.3 Special Accessories

No special accessories were needed in order to achieve compliance.

### 2.4 Equipment Modifications

No modifications were necessary in order to achieve compliance.

### 2.5 Configuration of Tested System




Figure 1. Radiated Test Set-Up



**POINTER**

## C2PC Declaration

Date: March, 3 2019

1. The E.U.T. was originally FCC certified on 07/02/2018 under FCC ID: 2AG69CTLL and IC certified on 7/24/2018 under IC: 9975A-CTLL.
2. The E.U.T contains 2 transceivers: a BLE, as certified above, and a 4G cellular approved module LTE/WCDMA module, manufactured by Gemalto M2M GmbH, model Cinterion ELS61-US, FCC ID: QIPELS61-US, IC: 7830A-ELS61US.
3. Pointer Telocation has replaced the above Gemalto 4G cellular module with the following LTE/WCDMA module, also manufactured by Gemalto M2M GmbH, model Cinterion ELS61-USA, FCC ID: QIPELS61-USA, IC: 7830A-ELS61USA.

Based on the above change, Pointer Telocation requests a C2PC.

Thank you,

Igor Rogov, VP R&D,  
Pointer Telocation

~~IGOR ROGOV  
7/24/2019  
VP R&D~~



### 3. Test Set-Up Photos



**Figure 2. Intermodulated Radiated Emission Test**

## 4. Intermodulation Radiated

### 4.1 Test Procedure

(Temperature (24°C)/ Humidity (49%RH))

The test method was based on ANSI/TIA-603-D: 2010, Section 2.2.12 Unwanted Emissions: Radiated Spurious.

The E.U.T was tested inside the shielded room at a distance of 3 meters and the E.U.T was placed on a non-metallic table, 1.5 meters above the ground. The frequency range 1.0GHz -18.0GHz was scanned. The readings were maximized by the turntable azimuth between 0-360°, and the antenna polarization. The emissions were measured at a distance of 3 meters.

The E.U.T. was replaced by a substitution antenna (dipole 30MHz-1GHz, Horn Antenna above 1GHz) driven by a signal generator. The height was readjusted for maximum reading. The signal generator level was adjusted to obtain the same reading on the EMI receiver as in step (a).

The signals observed in step (a) were converted to radiated power using:

$$P_d(\text{dBm}) = P_g(\text{dBm}) - \text{Cable Loss (dB)} + \text{Substitution Antenna Gain (dB)}$$

$P_d$  = Dipole equivalent power (result).

$P_g$  = Signal generator output level.

A Peak detector was used for this test.

The table on the following page describes only results with the highest radiation.

### 4.2 Test Limit

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 * \log (P)$  dB, yielding -13dBm.

### 4.3 Test Results

JUDGEMENT: Passed

## Intermodulation Radiated

Freq.	Pol.	Maximum Peak Level	Signal Generator RF Output	Cable Loss	Antenna Gain	ERP Level	Limit	Margin
(MHz)	(V/H)	(dB $\mu$ V/m)	(dBm)	(dB)	(dBd)	(dBm)	(dBm)	(dB)
926.0	V	46.2	-55.4	0.5	5.0	-50.9	-13.0	-37.9
	H	47.0	-53.0	0.5	5.0	-48.5	-13.0	-35.5
1418.0	V	47.7	-51.4	0.5	4.9	-47.0	-13.0	-34.0
	H	48.1	-51.0	0.5	4.9	-46.6	-13.0	-33.6
2894.0	V	56.0	-48.6	1.0	7.9	-41.7	-13.0	-28.7
	H	55.7	-48.5	1.0	7.9	-41.6	-13.0	-28.6
3386.0	V	53.1	-51.6	1.0	7.9	-44.7	-13.0	-31.7
	H	53.3	-51.5	1.0	7.9	-44.6	-13.0	-31.6
3878.0	V	56.8	-48.0	1.0	7.4	-41.6	-13.0	-28.6
	H	57.2	-48.0	1.0	7.4	-41.6	-13.0	-28.6
4370.0	V	56.4	-49.0	1.0	7.4	-42.6	-13.0	-29.6
	H	56.2	-49.0	1.0	7.4	-42.6	-13.0	-29.6

**Figure 3 Intermodulation Radiated Results**

**4.4 Test Instrumentation Used; Radiated Measurements Intermodulation**

Instrument	Manufacturer	Model	Serial Number	Calibration	
				Last Calibration Date	Next Calibration Due
EMI Receiver	HP	85422E	3906A00276	February 19, 2018	February 28, 2019
RF Filter Section	HP	85420E	3705A00248	February 19, 2018	February 28, 2019
EMI Receiver	R&S	ESCI7	100724	February 19, 2018	February 28, 2019
Spectrum Analyzer	HP	8593EM	3536A00120ADI	February 20, 2018	February 28, 2019
Antenna Biconical	EMCO	3110B	9912-3337	May 31, 2018	May 31, 2019
Antenna Log Periodic	EMCO	3146	9505-4081	May 31, 2018	May 31, 2019
Horn Antenna 1G-18G	ETS	3115	29845	May 31, 2018	May 31, 2021
Signal Generator	WILTRON	6747B	278007	February 20, 2018	February 20, 2019
Signal Generator	HP	8648C	3623A04126	February 19, 2018	February 28, 2019
Semi Anechoic Civil Chamber	ETS	S81	SL 11643	NCR	NCR
Antenna Mast	ETS	2070-2	-	NCR	NCR
Turntable	ETS	2087	-	NCR	NCR
Mast & Table Controller	ETS/EMCO	2090	9608-1456	NCR	NCR

**Figure 4 Test Equipment Used**



## 5. Antenna Information/Gain

BLE Chip, 1.72 dBi max

Cellular GSM, 2.15 dBi

## 6. RF Exposure/Safety

The typical placement of the E.U.T. is on a container. The typical distance between the E.U.T. and the user is at least 20cm.

Calculation of Maximum Permissible Exposure (MPE)

Based on Section 1.1310 Requirements

(a) FCC limits for 1.5GHz-100GHz is:  $1 \frac{mW}{cm^2}$

Using table 1 of Section 1.1310 limit for general population/uncontrolled exposures, the above level is an average over 30 minutes.

(b) The power density produced by the E.U.T. is

$$S = \frac{P_t G_t}{4\pi R^2}$$

$P_t$ - Transmitted Peak Power

$G_t$ - Antenna Gain

$R$ - Distance from Transmitter (using 20cm worst case)

### **For cellular transmitter:**

Conducted power (worst case) – 0.22W + 10% = 242mW

Antenna gain 2.15dBi = 1.64059 numeric

$$S_1 = 242 \times 1.64 / 4\pi(400) = 0.079 \text{ mw/cm}^2$$

### **For 2.4GHz transmitter:**

Conducted power (worst case) – 6.5dbm = 4.47mW

Antenna gain 1.72dBi = 1.49numeric

$$S_2 = 4.47 \times 1.49 / 4\pi(400) = 0.001 \text{ mw/cm}^2$$

### **Co-located RF exposure**

$$S_1 + S_2 = 0.079 + 0.001 = 0.08 \text{ mw/cm}^2$$

All are below the FCC/IC limit

## 7. APPENDIX A - CORRECTION FACTORS

### 7.1 Correction factor for RF CABLE for Semi Anechoic Chamber

ITL # 1841

FREQ (MHz)	LOSS (dB)
1000.0	1.5
2000.0	2.1
3000.0	2.7
4000.0	3.1
5000.0	3.5
6000.0	4.1
7000.0	4.6
8000.0	4.9
9000.0	5.7
10000.0	5.7
11000.0	6.1
12000.0	6.1
13000.0	6.2
14000.0	6.7
15000.0	7.4
16000.0	7.5
17000.0	7.9
18000.0	8.1
19000.0	8.8
20000.0	9.1

**NOTES:**

1. The cable is manufactured by Commscope
2. The cable type is 0623 WBC-400, serial # G020132 and 10m long



**7.2 Correction factors for biconical antenna – ITL # 1356**

**Model: EMCO 3110B**

**Serial No.:9912-3337**

<b>Frequency</b>	<b>ITL 1356 AF</b>
<b>[MHz]</b>	<b>[dB/m]</b>
<b>30</b>	13.00
<b>35</b>	10.89
<b>40</b>	10.59
<b>45</b>	10.63
<b>50</b>	10.12
<b>60</b>	9.26
<b>70</b>	7.74
<b>80</b>	6.63
<b>90</b>	8.23
<b>100</b>	11.12
<b>120</b>	13.16
<b>140</b>	13.07
<b>160</b>	14.80
<b>180</b>	16.95
<b>200</b>	17.17





**7.3 Correction factors for log periodic antenna – ITL # 1349**

**Model: EMCO 3146**

**Serial No.:9505-4081**

<b>Frequency</b>	<b>ITL 1349 AF</b>
<b>[MHz]</b>	<b>[dB/m]</b>
200	11.58
250	12.04
300	14.76
400	15.55
500	17.85
600	18.66
700	20.87
800	21.15
900	22.32
1000	24.22



**7.4 Correction factors for  
Horn ANTENNA**

**Double –Ridged Waveguide**

**Model: 3115  
Serial number:29845  
3 meter range; ITL # 1352**

<b>FREQUENCY</b>	<b>APE</b>	<b>FREQUENCY</b>	<b>APE</b>
<b>(GHz)</b>	<b>(dB/m)</b>	<b>(GHz)</b>	<b>(dB/m)</b>
0.75	25	9.5	38
1.0	23.5	10.0	38.5
1.5	26.0	10.5	38.5
2.0	29.0	11.0	38.5
2.5	27.5	11.5	38.5
3.0	30.0	12.0	38.0
3.5	31.5	12.5	38.5
4.0	32.5	13.0	40.0
4.5	32.5	13.5	41.0
5.0	33.0	14.0	40.0
5.5	35.0	14.5	39.0
6.0	36.5	15.0	38.0
6.5	36.5	15.5	37.5
7.0	37.5	16.0	37.5
7.5	37.5	16.5	39.0
8.0	37.5	17.0	40.0
8.5	38.0	17.5	42.0
9.0	37.5	18.0	42.5